

CLAIMS

1. An electronic device (100), comprising:
 - 5 a first wireless transceiver module (120) using a first communication protocol;
 - a second wireless transceiver module (140) using a second communication protocol, the second wireless transceiver module (140) comprising a controller for avoiding an interference with an external signal on a
 - 10 frequency of the second communication protocol; and
 - a mediator (160) coupled between the first wireless transceiver module (120) and the second wireless transceiver module (140), the mediator (160) being arranged to provide the controller with a blocking signal in response to an enabled communication involving the first wireless transceiver module
 - 15 (120).
2. An electronic device (100) as claimed in claim 1, wherein the controller implements at least a part of a carrier sense multiple access – collision avoidance principle.
- 20 3. An electronic device as claimed in claim 1, wherein the first wireless transceiver module (120) and the second wireless transceiver module (140) share at least a part of a physical layer (110).
- 25 4. An electronic device (100) as claimed in claim 1, wherein the mediator is arranged to provide the blocking signal during a time interval matching the duration of the enabled communication.
5. An electronic device (100) as claimed in claim 1 or 4, wherein the first
- 30 wireless transceiver module (120) comprises a further controller for avoiding an interference with a further external signal on a frequency of the first communication protocol;

the mediator (160) being further arranged to provide the further controller with a further blocking signal in response to a further enabled communication involving the second wireless transceiver module (140).

- 5 6. A method for controlling communications involving a communication system, the communication system comprising:

a first wireless transceiver module using a first communication protocol;

a second wireless transceiver module using a second communication protocol, the second wireless transceiver module comprising a controller for
10 avoiding an interference with an external signal on a frequency of the second communication protocol;

the method comprising the steps of:

detecting an enabled communication involving the first wireless transceiver module; and

15 providing the controller with a blocking signal in response to the enabled communication.

7. A communication system (300), comprising:

a wired network (360);

20 a first wireless transceiver module (320) coupled to the wired network (360) using a first communication protocol for communicating with a first external device (322);

a second wireless transceiver module (340) coupled to the wired network (360) using a second communication protocol for communicating with
25 a second external device (342), the second wireless transceiver module (360) comprising a controller for avoiding an interference with an external signal on a frequency of the second communication protocol; and

a mediator (380) coupled to the first wireless transceiver module (320) and the second wireless transceiver module (340) for providing the controller
30 with a blocking signal in response to an enabled communication involving the first wireless transceiver module (320).

8. A communication system (300) as claimed in claim 7, wherein the mediator (380) is coupled to the controller via the wired network (360).

9. A communication system (300) as claimed in claim 7 or 8, wherein the
5 first wireless transceiver module (320) comprises a further controller for avoiding an interference with a further external signal on a frequency of the first communication protocol; and

the mediator (380) is arranged to provide the further controller with a further blocking signal responsive to a further enabled communication
10 involving the second wireless transceiver module.

10. A communication system as claimed in claim 7, wherein the first transceiver module (320) and the second transceiver module (340) share at least a part of a physical layer.